



# APE VIBRO 300-6 HD

## DEEP FOUNDATION SOLUTIONS

# SILVERBACK™ TECHNOLOGY



SPECIFICATIONS	DATA
Eccentric Moment	8,000 in-lbs (92 kgm)
Drive Force	388tons (3,454 kN)
Frequency Maximum (VPM)	0 - 1,850 vpm
Max Line Pull	185 tons (1,646 kN)
Bare Hammer Weight w/o Clamp	21,200 lbs (9,616kg)
Throat Width	22.25 in (56.5cm)
Length	155.00 in (393.7cm)
Height w/o Clamp	81.6 in (207cm)

### APE Model Tier 4 950 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C 27 Tier IV
Horse Power	950 HP (699 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	265 gpm (1,003 lpm)
Clamp Pressure	4,800 psi (331 bar)
Clamp Flow	10 gpm (36 lpm)
Speed	1,800 rpm
Weight	27,000 lbs (12,247 kg)
Length	183 in (465 cm)
Width	88 in (224 cm)
Height	106 in (268 cm)
Hydraulic Reservoir	670 gal (2,536 L)
Fuel Capacity	170 gal (644 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice. Consult the factory for details on any specific product (800) 248-8498.

**WWW.AMERICANPILEDIVING.COM**  
(800) 248-8498  
ape@americanpilediving.com