

APE D100-42 Single Acting Diesel Impact Hammer

D100-42 in a bottom drive.



MODEL D100-42 (10.0 metric ton ram)

SPECIFICATIONS

Stroke at maximum rated energy	135 in (343 cm)
Maximum rated energy (Setting 4)	248,063 ft-lbs (334.88 kNm)
Setting 3	220,776 ft-lbs (298.05 kNm)
Setting 2	191,008 ft-lbs (257.86 kNm)
Minimum rated energy (Setting 1)	158,760 ft-lbs (214.33 kNm)

(Variable throttle allows for infinite fuel settings)

Maximum obtainable stroke	150 in (381 cm)
Maximum obtainable energy	288,488 ft-lbs (391 kNm)
Speed (blows per minute)	34-53

WEIGHTS (Approximate)

Ram	22,050 lbs (10,000 kg)
Anvil	4,670 lbs (2,118 kg)
Anvil cross sectional area	482.8 in ² (3114.83 cm ²)
Hammer weight (includes hydraulic trip device)	47,000 lbs (21,318 kg)
Typical operating (weight with offshore leader)	77,000 lbs (34,920 kg)

CAPACITIES

Fuel tank (runs on diesel or bio-diesel)	40.3 gal (153 liters)
Oil tank	8.3 gal (31.5 liters)

CONSUMPTION

Diesel or Bio-diesel fuel	7.8 gal/hr (30 liters/hr)
Lubrication	0.67 gal/hr (2.5 liters/hr)
Grease	8 to 10 pumps every 20 minutes of operation time.


Optional Variable Throttle Control.



STRIKER PLATE

Weight	1,036 lbs (470 kg)
Diameter	25 in (57.15 cm)
Area	491 in ² (3167.74 cm ²)
Thickness	8 in (20.32 cm)

Cushion material.



CUSHION MATERIAL

Type/Qty	Micarta / 2 each
Diameter	25 in (57.15 cm)
Thickness	1 in (25.4 mm)
Type/Qty	Aluminum / 3 each
Thickness	1/2 in (12.7 mm)
Diameter	25 in (57.15 cm)
Total Combined Thickness	3.5 in (8.89 cm)
Area	491 in ² (3167.74 cm ²)
Elastic-modulus	285 ksi (1,965 mpa)
Coeff. of restitution	0.8

Typical 54" offshore.



STANDARD OFFSHORE LEADER

8"x54" for 48" piles and under	Consult Factory
--------------------------------	-----------------

MINIMUM BOX LEAD SIZE/OPERATING LENGTH

Minimum box leader size	8 in x 37 in (20.32 cm x 94 cm)
Operating length for offshore leader	396 in (1005.84 cm)



Corporate Offices
7032 South 196th
Kent, Washington 98032 USA
(800) 248-8498 & (253) 872-0141
(253) 872-8710 Fax

Visit our WEB site:
www.apevibro.com
e-mail: ape@apevibro.com