



APE Model 20 Top Drive Auger

The Worlds Largest Provider of Foundation Construction Equipment



Specifications		Standard	Metric
Low Speed High Torque	Torque	4,200 ft-lbs per 1000 psi	581 kgm per 69 bar
	Max Pressure	5,000 psi	345 bar
	Rotation Speed	50 rpm	
	Max Flow	55 gpm @ 1.11 gal / rev	208 lpm @ 4.2 lit / rev
	Max Horse Power	144 hp	107.38 kW
High Speed Low Torque	Torque	1,546 ft-lbs per 1000 psi	214 kgm per 69 bar
	Max Pressure	3,500 psi	241 bar
	Rotation Speed	99 rpm	
	Max Flow	55 gpm @ 0.55 gal / rev	208 lpm @ 2.08 lit / rev
	Max Horse Power	96 hp	71.59 kW
Crowd Force		77,000 lbs	34,927 kg
Suspensid Weight		4,310 lbs	1,955 kg
Length		25 in	64 cm
Width (Lead Section)		26 in	66 cm
Width (Overall)		48 in	122 cm
Height		62 in	156 cm
ID of Output Shaft		3 in	8 cm
ID of Rotary Joint		3 in	8 cm
API Adapters		API 3 inch, API 4 inch	
Lead Adapters		8 x 26, 8 x 32	

WWW.APEVIBRO.COM

(800) 248-8498

webmaster@apevibro.com



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.