



# APE Model 75BB Top Drive Auger

The Worlds Largest Provider of  
Foundation Construction Equipment



Specifications		Standard	Metric
Low Speed High Torque	Torque	12,150 ft-lbs per 1000 psi	1,680 kgm per 69 bar
	Max Pressure	5,800 psi	400 bar
	Rotation Speed	30 rpm	
	Max Flow	120 gpm @ 4.17 gal / rev	454 lpm @ 15.79 lit / rev
	Max Horse Power	508 hp	378.82 kW
High Speed Low Torque	Torque	6,075 ft-lbs per 1000 psi	840 kgm per 69 bar
	Max Pressure	5,800 psi	400 bar
	Rotation Speed	60 rpm	
	Max Flow	120 gpm @ 2.09 gal / rev	454 lpm @ 7.91 lit / rev
	Max Horse Power	406 hp	302.75 kW
Crowd Force		150,000 lbs	68,039 kg
Suspendid Weight		4,630 lbs	2,100 kg
Length		25 in	64 cm
Width (Lead Section)		26 in	66 cm
Width (Overall)		48 in	122 cm
Height		62 in	156 cm
ID of Output Shaft		3 in	8 cm
ID of Rotary Joint		3 in	8 cm
API Adapters		3 inch, 4 inch	
Lead Adapters		8 x 26, 8 x 32 Custom Available	

**WWW.APEVIBRO.COM**  
(800) 248-8498  
webmaster@apevibro.com



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice.  
Consult the factory for details on any specific product (800) 248-8498.

