



APE Model 20BB Top Drive Auger

The Worlds Largest Provider of
Foundation Construction Equipment



Specifications		Standard	Metric
Low Speed High Torque	Torque	4,844 ft-lbs per 1000 psi	670 kgm per 69 bar
	Max Pressure	5,500 psi	379 bar
	Rotation Speed	40 rpm	
	Max Flow	66 gpm @ 1.11 gal / rev	250 lpm @ 4.2 lit / rev
	Max Horse Power	212 hp	158.09 kW
High Speed Low Torque	Torque	2,422 ft-lbs per 1000 psi	335 kgm per 69 bar
	Max Pressure	5,500 psi	379 bar
	Rotation Speed	80 rpm	
	Max Flow	66 gpm @ 0.55 gal / rev	250 lpm @ 2.08 lit / rev
	Max Horse Power	212 hp	158.09 kW
Crowd Force		77,000 lbs	34,927 kg
Suspendid Weight		4,310 lbs	1,955 kg
Length		25 in	64 cm
Width (Lead Section)		26 in	66 cm
Width (Overall)		48 in	122 cm
Height		62 in	156 cm
ID of Output Shaft		3 in	8 cm
ID of Rotary Joint		3 in	8 cm
API Adapters		API 3 inch, API 4 inch	
Lead Adapters		8 x 26, 8 x 32	

WWW.APEVIBRO.COM
(800) 248-8498
webmaster@apevibro.com



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.

