



APE Model 75 Top Drive Auger

The Worlds Largest Provider of
Foundation Construction Equipment



Specifications		Standard	Metric
Low Speed High Torque	Torque	11,516 ft-lbs per 1000 psi	1,592 kgm per 69 bar
	Max Pressure	4,640 psi	320 bar
	Rotation Speed	30 rpm	
	Max Flow	120 gpm @ 3.96 gal / rev	454 lpm @ 14.99 lit / rev
	Max Horse Power	325 hp	242.35 kW
High Speed Low Torque	Torque	5,940 ft-lbs per 1000 psi	821 kgm per 69 bar
	Max Pressure	3,000 psi	207 bar
	Rotation Speed	61 rpm	
	Max Flow	120 gpm @ 1.98 gal / rev	454 lpm @ 7.5 lit / rev
	Max Horse Power	210 hp	156.6 kW
Crowd Force		150,000 lbs	68,039 kg
Suspendid Weight		4,630 lbs	2,100 kg
Length		25 in	64 cm
Width (Lead Section)		26 in	66 cm
Width (Overall)		48 in	122 cm
Height		62 in	156 cm
ID of Output Shaft		3 in	8 cm
ID of Rotary Joint		3 in	8 cm
API Adapters		API 3 inch, API 4 inch	
Lead Adapters		8 x 26, 8 x 32	

WWW.APEVIBRO.COM
(800) 248-8498
webmaster@apevibro.com



Specifications may vary due to site conditions, specific hammer conditions or product set up. Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.

