



APE Model 200 Low-Headroom Vibratory Driver Extractor

The Worlds Largest Provider of Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	4,400 in-lbs (50.69 kgm)
Drive Force	170 tons (1,513 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	<u>Consult Factory</u>
Bare Hammer Weight w/o Clamp	<u>Consult Factory</u>
Throat Width	<u>Consult Factory</u>
Length	<u>Consult Factory</u>
Height w/o Clamp	<u>Consult Factory</u>

APE Model 765 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C18 Tier II
Horse Power	765 HP (563 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	220 gpm (833 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	20,000 lbs (9,072 kg)
Length	152 in (385 cm)
Width	82 in (208 cm)
Height	94 in (239 cm)
Hydraulic Reservoir	450 gal (1,703 L)
Fuel Capacity	150 gal (568 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.
 Specifications may change without notice.
 Consult the factory for details on any specific product (800) 248-8498.



