



## APE Model 15 Vibratory Driver Extractor

The Worlds Largest Provider of  
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	600 in-lbs (6.91 kgm)
Drive Force	23 tons (206 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	9 tons (80 kN)
Bare Hammer Weight w/o Clamp	2,000 lbs (907 kg)
Throat Width	9.00 in (23 cm)
Length	36.50 in (93 cm)
Height w/o Clamp	49.75 in (126 cm)

## APE Model 127 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C4.4Tier IV
Horse Power	127 HP (93 kW)
Drive Pressure	0 - 2,500 psi (172 bar)
Drive Flow	60 gpm (227 lpm)
Clamp Pressure	<u>Consult Factory</u>
Clamp Flow	<u>Consult Factory</u>
Engine Speed	2,200 rpm
Weight	4,750 lbs (2,155 kg)
Length	99 in (251 cm)
Width	45 in (114 cm)
Height	66 in (168 cm)
Hydraulic Reservoir	140 gal (530 L)
Fuel Capacity	75 gal (284 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.  
Specifications may change without notice.  
Consult the factory for details on any specific product (800) 248-8498.



**WWW.AMERICANPILEDIVING.COM**

(800) 248-8498

ape@americanpiledriving.com