



APE Model 20 Vibratory Driver Extractor

The Worlds Largest Provider of
Foundation Construction Equipment



| SPECIFICATIONS | DATA |
|------------------------------|------------------------|
| Eccentric Moment | 900 in-lbs (10.37 kgm) |
| Drive Force | 35 tons (310 kN) |
| Frequency Maximum (VPM) | 0 - 1,650 vpm |
| Max Line Pull | 28 tons (249 kN) |
| Bare Hammer Weight w/o Clamp | 2,510 lbs (1,139 kg) |
| Throat Width | 12.00 in (30 cm) |
| Length | 36.50 in (93 cm) |
| Height w/o Clamp | 45.00 in (114 cm) |

APE Model 275 Power Unit

| SPECIFICATIONS | DATA |
|---------------------|-------------------------|
| Engine Type | Caterpillar C7 Tier III |
| Horse Power | 275 HP (202 kW) |
| Drive Pressure | 0 - 4,800 psi (331 bar) |
| Drive Flow | 74 gpm (280 lpm) |
| Clamp Pressure | 4,800 psi (69,618 bar) |
| Clamp Flow | 10 gpm (3 lpm) |
| Engine Speed | 2,100 rpm |
| Weight | 11,500 lbs (5,216 kg) |
| Length | 117 in (296 cm) |
| Width | 59 in (149 cm) |
| Height | 84 in (212 cm) |
| Hydraulic Reservoir | 225 gal (852 L) |
| Fuel Capacity | 80 gal (303 L) |



Specifications may vary due to site conditions, specific hammer conditions or product set up.
Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.



WWW.AMERICANPILEDIVING.COM

(800) 248-8498

ape@americanpiledriving.com