



## APE Model 300 Vibratory Driver Extractor

The Worlds Largest Provider of  
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	5,750 in-lbs (66.25 kgm)
Drive Force	160 tons (1,424 kN)
Frequency Maximum (VPM)	0 - 1,400 vpm
Max Line Pull	150 tons (1,334 kN)
Bare Hammer Weight w/o Clamp	19,500 lbs (8,845 kg)
Throat Width	14.00 in (36 cm)
Length	110.00 in (279 cm)
Height w/o Clamp	106.00 in (269 cm)

## APE Model 765 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C18 Tier II
Horse Power	765 HP (563 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	220 gpm (833 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	20,000 lbs (9,072 kg)
Length	152 in (385 cm)
Width	82 in (208 cm)
Height	94 in (239 cm)
Hydraulic Reservoir	450 gal (1,703 L)
Fuel Capacity	150 gal (568 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.  
Specifications may change without notice.  
Consult the factory for details on any specific product (800) 248-8498.



[WWW.AMERICANPILEDIVING.COM](http://WWW.AMERICANPILEDIVING.COM)

(800) 248-8498

[ape@americanpiledriving.com](mailto:ape@americanpiledriving.com)

