



# APE Model 3 Vibratory Driver Extractor

## The Worlds Largest Provider of Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	30 in-lbs (.35 kgm)
Drive Force	2 tons (18 kN)
Frequency Maximum (VPM)	0 - 2,200 vpm
Max Line Pull	6 tons (53 kN)
Bare Hammer Weight w/o Clamp	450 lbs (204 kg)
Throat Width	6.00 in (15 cm)
Length	27.63 in (70 cm)
Height w/o Clamp	38.00 in (97 cm)

## APE Model 10 Power Unit

SPECIFICATIONS	DATA
Engine Type	Yanmar
Horse Power	10 HP (7 kW)
Drive Pressure	0 - 3,500 psi (241 bar)
Drive Flow	6 gpm (22 lpm)
Clamp Pressure	3,500 psi (50,763 bar)
Clamp Flow	6 gpm (2 lpm)
Engine Speed	3,000 rpm
Weight	275 lbs (125 kg)
Length	24 in (61 cm)
Width	32 in (80 cm)
Height	42 in (107 cm)
Hydraulic Reservoir	20 gal (76 L)
Fuel Capacity	Consult Factory



Specifications may vary due to site conditions, specific hammer conditions or product set up.  
 Specifications may change without notice.  
 Consult the factory for details on any specific product (800) 248-8498.



WWW.AMERICANPILEDIVING.COM  
 (800) 248-8498  
 ape@americanpilediving.com