



APE Model 400P2 Vibratory Driver Extractor

The Worlds Largest Provider of Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	11,500 in-lbs (132.49 kgm)
Drive Force	298 tons (2,648 kN)
Frequency Maximum (VPM)	0 - 1,350 vpm
Max Line Pull	234 tons (2,082 kN)
Bare Hammer Weight w/o Clamp	31,570 lbs (14,320 kg)
Throat Width	33.00 in (84 cm)
Length	141.00 in (358 cm)
Height w/o Clamp	88.50 in (225 cm)

APE Model 1200 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C32 Tier II
Horse Power	1,200 HP (883 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	294 gpm (1,113 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	23,000 lbs (10,433 kg)
Length	169 in (428 cm)
Width	87 in (221 cm)
Height	103 in (262 cm)
Hydraulic Reservoir	760 gal (2,877 L)
Fuel Capacity	180 gal (681 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.
 Specifications may change without notice.
 Consult the factory for details on any specific product (800) 248-8498.



WWW.AMERICANPILEDIVING.COM

(800) 248-8498

ape@americanpilediving.com