



APE Model 50 Tandem Vibratory Driver Extractor

The Worlds Largest Provider of
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	2,600 in-lbs (29.96 kgm)
Drive Force	101 tons (894 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	112 tons (996 kN)
Bare Hammer Weight w/o Clamp	<u>Consult Factory</u>
Throat Width	<u>Consult Factory</u>
Length	<u>Consult Factory</u>
Height w/o Clamp	<u>Consult Factory</u>

APE Model 475 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C13 Tier III
Horse Power	475 HP (349 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	147 gpm (556 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	14,750 lbs (6,690 kg)
Length	128 in (324 cm)
Width	74 in (187 cm)
Height	92 in (234 cm)
Hydraulic Reservoir	305 gal (1,155 L)
Fuel Capacity	117 gal (443 L)





WWW.AMERICANPILEDIVING.COM

(800) 248-8498

ape@americanpiledriving.com