



## APE Model 150T Vibratory Driver Extractor

The Worlds Largest Provider of  
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	2,600 in-lbs (29.96 kgm)
Drive Force	101 tons (894 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	108 tons (961 kN)
Bare Hammer Weight w/o Clamp	8,500 lbs (3,856 kg)
Throat Width	14.25 in (36 cm)
Length	88.75 in (225 cm)
Height w/o Clamp	72.38 in (184 cm)

## APE Model 475 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C13 Tier III
Horse Power	475 HP (349 kW)
Drive Pressure	0 - 4,500 psi (310 bar)
Drive Flow	147 gpm (556 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	14,750 lbs (6,690 kg)
Length	128 in (324 cm)
Width	74 in (187 cm)
Height	92 in (234 cm)
Hydraulic Reservoir	305 gal (1,155 L)
Fuel Capacity	117 gal (443 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.  
Specifications may change without notice.  
Consult the factory for details on any specific product (800) 248-8498.



**WWW.AMERICANPILEDIVING.COM**

(800) 248-8498

ape@americanpiledriving.com